

# mazore

Trading Ltd

*distance under control*

## **Radio-switch<sub>pro</sub>**

### Transmitter-Receiver Set for Wireless Control of a Remote Surveillance Module

The radio-switchpro is typically used for the following reasons:

- activate/de-activate a remote surveillance module
- set off an alarm

The devices are characterised by an especially large coverage range of up to 100 metres under good free field conditions.

All remote-surveillance modules are compatible with the receiver of the radio-switchpro.

Each radio-switchpro is individually encoded. With more than 70 million code possibilities, it is 100% certain that your code is really unique.

Each receiver can accommodate an unlimited number of radio-switchpro handheld transmitters.



**Handheld Transmitter**



**Receiver**

If needed, the coding can be changed by the user.

If a device is lost, a new code can be generated in order to inhibit misuse.

### **Technical Data of the**

---

**Mazore Trading Ltd. - Krinon 16 - 3110 Ekali – Limassol/Cyprus**

Sales and information: e-mail: [info@mazore.com](mailto:info@mazore.com) - website: [www.mazore.com](http://www.mazore.com)

Almere/The Netherlands tel: +31-36-5387090 - fax: +31-36-5387099

Oberhausen/Germany tel: +49-208-6986088 - fax: +49-208-6986087

## Transmitter

<b>Encoding</b>	Programmed with over 70 million code possibilities, user-coding also possible
<b>Frequency</b>	433,92 MHz, 868,30 MHz (alternatively)
<b>Channels</b>	Button 1: activate theft protection Button 2: de-activate theft protection Button 3: set off alarm
<b>Modulation</b>	ASK
<b>Coverage</b>	In good free field conditions up to 100 metres possible
<b>Power Supply</b>	1 x 3-V battery, CR 2032
<b>Operation Control</b>	Light emitting diode (LED)
<b>Temperature Range</b>	-20°C to +60°C (satisfies the temperature range of the remote surveillance device)
<b>Dimensions</b>	70 x 40 x 17 mm
<b>Weight</b>	ca. 25 g (including batteries)

## Technical Data of the Receiver

<b>Power Supply</b>	12-24V AC/DC
<b>Max. Current Consumption</b>	ca. 50mA
<b>Closed Current</b>	ca. 16 mA
<b>Output Load</b>	60V DC/1A/30W 125V AC/1A/62VA
<b>Temperature Range</b>	-20°C ... +60°C

## Products

<b>Product</b>	<b>Part-No.</b>	<b>Product Description</b>	<b>Price</b>
radio-switchpro	ZUB-04-01	Transmitter and receiver to control a remote surveillance module.	98,--
transmitter pro	ZUB-04-02	Additional handheld transmitter for radio-switchpro. An unlimited number of transmitters can be used.	49,--